



**FF500 SALLYPORT/SECURITY (GRILL)
FOUR-FOLD DOOR GENERAL LAYOUT
OPERATOR: R-SERIES, ELECTRO-MECHANICAL**

This layout is designed as a guide for required clearances for our standard Four-Fold Door systems. Many standard and custom grill options and layouts are available. Contact us to discuss additional options and for custom clearance requirements or larger opening sizes.

DOOR WIDTHS	CLEARANCES				MAX. TIME TO OPEN	MOTOR HP	OPERATOR SIZE
	A	B	C	D			
7'-6" to 10'-6"	13"	1/4 OPENING PLUS 12"	29"	15"	5.3 sec	1/2	R1
10'-6" to 13'-6"	15"		40"	16"	7.7 sec	1/2	R2
13'-6" to 16'-0"	15"		42"	16"	7.7 sec	3/4	R3
16'-0" to 17'-3"	15"		42"	17"	11.2 sec	3/4	R3-10"
17'-3" to 23'-0"	21"		65"	18"	15.4 sec	1	R3.5

*Consult manufacturer for larger sizes or modified clearances



400 West Cherry Street,
P.O. Box 5
Kasota, MN 56050-0005

Phone: 507-931-6910
Fax: 507-931-9318
Toll Free: 800-959-1352